

Name: YOUR NAME HERE

CS46 lab 6

This homework is due at 11:59PM on Tuesday, 3 March. This is a **10 point** homework.

You may work with one partner on this lab. Your write-up is your own: do not share it, and do not read other teams' write-ups. If you use any out-of-class references (anything except class notes, the textbook, or asking the instructor), then you **must** cite these in your post-lab survey. Please refer to the course webpage or ask me any questions you have about this policy.

The main **learning goal** of this homework is to work with and think about context-free languages, and to practice using the Pumping Lemma for Context-Free Languages.

1. The textbook (example 2.38) shows that the language

$$L = \{ww \mid w \in \{0,1\}^*\}$$

is not context-free. Prove that \bar{L} is context-free. (Note: This shows that the context-free languages are *not* closed under complementation! We also saw a counterexample of this in practice problems 6. Also note: this language's alphabet does not include #, so it is different from the problem you saw on lab. Be careful! We've seen examples where one character makes a big difference.)

2. Using the stack in a PDA can be subtle. One way to see this is examine two languages that are *very* similar, and show that they require different computational power to recognize. (Hint: the difference is going to be in the usage of the stack!)

Note that:

- i and j are not necessarily distinct in part (a)
- any palindrome x satisfies $x = x^R$
- $|x_i|$ can be zero for any i

- (a) Give a context-free grammar that generates (or pushdown automata that recognizes) the language:

$$\{t_1\#t_2\#\cdots\#t_k \mid k \geq 1, \text{ each } t_i \in \{a,b\}^*, \text{ and } t_i = t_j^R \text{ for some } i, j\}$$

You do not have to prove the correctness of your grammar/PDA, but you should give a high-level explanation of why/how you designed it, and why both directions of proof should work.

- (b) Use the pumping lemma to show that the following language is not context-free:

$$\{t_1\#t_2\#\cdots\#t_k \mid k \geq 2, \text{ each } t_i \in \{a,b\}^*, \text{ and } t_i = t_j \text{ for some } i \neq j\}$$

- (c) (**extra challenge**) Use closure properties to show that the language from part (b) is not context-free.

3. (extra challenge) Inspired by genetics, define the CROSSOVER operator as follows:

$$\text{CROSSOVER}(A, B) = \{x_1y_2, x_2y_1 \mid x_1x_2 \in A, y_1y_2 \in B, \text{ and } |x_1| = |x_2| = |y_1| = |y_2|\}$$

So for every pair of equal-length strings $x_1x_2 \in A$ and $y_1y_2 \in B$, we add two strings to the crossover language by cutting them in half and recombining them.

For example, if $A = \{a, aa, aabb\}$ and $B = \{\varepsilon, cc, caca, aacaa\}$ then $\text{CROSSOVER}(A, B) = \{ac, ca, aaca, cabb\}$.

Show that if A and B are regular, then $\text{CROSSOVER}(A, B)$ is not necessarily regular.

Show that if A and B are regular, then $\text{CROSSOVER}(A, B)$ is context-free.